

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: Class CI Fly Ash

Synonyms: Subbituminous Coal Flyash

Supplier/Manufacturer: Pozzolan International Limited
P.O. Box 950,
Delta, British Columbia,
Canada, V4K 3S6
Telephone 604-946-3842

ISG Resources, Inc.
Centralia Plant
Washington, USA
Telephone 770-424-1900

Emergency Contact Information: Pozzolan International Limited
P.O. Box 950,
Delta, British Columbia,
Canada, V4K 3S6
Telephone 604-946-3842

ISG Resources, Inc.
Centralia Plant
Washington, USA
Telephone 800-241-7799

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Formula	% ⁽¹⁾	OSHA PEL ⁽²⁾	ACGIH TLV ⁽²⁾
Aluminosilicate Glass	(Contains Si, Al, Fe, Ca, Mg, Ti)	85-95	Not Listed ⁽³⁾	Not Listed ⁽³⁾
Crystalline Silica (total)	SiO ₂	1-2	30/% SiO ₂ +2 ⁽⁴⁾	0.3
Crystalline Silica (respirable)	SiO ₂	Note 5	10/% SiO ₂ +2 ⁽⁴⁾	0.1
Iron Mineral	Fe ₂ O ₃	2-5	10	5
Lime	CaO	2-10	5	2
Magnesia	MgO	<6	15	10
Titania	TiO ₂	<5	15	10
Sodium Oxide	Na ₂ O	<4	Not Listed	Not Listed

Notes:

(1) Values approximate, this fly ash is the product of combustion of subbituminous coal. It is a complex inorganic substance composed, primarily, of compounds of the elements silicon, aluminum, iron, and calcium, with smaller amounts of magnesium, titanium, sodium, and potassium. This fly ash has not been classified by particle size.

(2) Airborne exposure limits in mg/m³.

(3) Not listed specifically by substance name. Exposure to Aluminosilicate glass dust may be covered by inert or nuisance dust limits of 15 mg/m³ for total dust and 5 mg/m³ for respirable portion.

(4) The percentage of crystalline silica in the formula is the amount determined from airborne samples.

(5) Presence of respirable crystalline silica has not been established.

SECTION 3 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Fine Brownish-Grey Powder

Odor: Odorless

Solubility In Water: Slight

Water Reactive: Not Reactive

Vapor Pressure(mmHg and Temperature): N/AP

Vapor Density(Air = 1): N/AP

Boiling Point: N/AP

Melting Point: >1990 F

Specific Gravity (H₂O = 1): 2.2-2.5

Evaporation Rate: N/AP

SECTION 4 - FIRE-AND EXPLOSION DATA

Flammability Limits in Air % by Volume:	N/AP
Flash Point & Method Used:	N/AP
LEL:	N/AP
UEL:	N/AP
Auto ignition Temperature:	N/AP
Extinguishing Media:	Use extinguishing matter suitable for surrounding fire.
Special Fire-Fighting Procedures:	N/AP
Unusual Fire And Explosion Hazards:	None, this mineral matter is considered non-flammable and non-combustible. Use fire extinguishing agent suitable for surrounding media.

SECTION 5 - STABILITY AND REACTIVITY

Stability:	Considered to be stable.
Conditions To Avoid:	None.
Hazardous Decomposition Products:	Decomposition products are unknown and not suspected.
Hazardous Polymerization:	Hazardous polymerization not known to occur.
Reactivity:	Material is considered inert.

SECTION 6 - TOXICOLOGICAL INFORMATION

Hazardous:	Is not considered hazardous.
Primary Routes Of Entry:	
Inhalation	Can be inhaled.
Ingestion	Can be ingested.
Skin and Eye Contact	Can irritate.
Signs and Symptoms of Exposure:	Irritation of eyes, skin, and respiratory system.
Health Hazards:	
Acute	Fly ash may cause irritation to the respiratory tract, eyes, or the skin.
Chronic	Repeated, prolonged inhalation may cause lung fibrosis
Medical Conditions Generally Aggravated by Exposure:	May aggravate existing pulmonary condition if high dust situation is created. Dusting conditions should not occur under normal use.
Carcinogen Listed In:	
NTP	Yes (Crystalline Silica)*
IARC Monograph	Yes (Crystalline Silica)*
OSHA	No

* Respirable crystalline silica is listed as a carcinogen. Presence of crystalline silica in respirable dust has not been established. Crystalline silica is classified as an IARC Group 1 carcinogen, for which there is sufficient evidence in humans.

SECTION 7 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection:	Use respirators NIOSH approved for pneumoconiosis- producing dusts.
Protective Gloves:	Limit contact with skin. Use rubber or cloth gloves as necessary.
Eye Protection:	Wear goggles or face shield as appropriate. Avoid contact lenses.
Ventilation To Be Used:	Keep dust levels below PEL. Use general and local exhaust ventilation and dust collection systems to keep dust levels within acceptable limits.
Other Protective Clothing And Equipment:	Industrial hygiene survey of other exposures would provide data needed to determine other precautions.

MATERIAL SAFETY DATA SHEET

Hygienic Work Practices:

Do not allow dust to get into eyes, to be inhaled, to be swallowed, or to remain on skin if irritation occurs. Minimize dusting. Practice good personal hygiene. Wash or shower after use. Launder clothes as normal.

Other Precautions And/Or Special Hazards:

Certain conditions (e.g. work in enclosed areas) could create over exposure to trace elements. These activities should be evaluated for compliance with applicable standards.

Steps To Be Taken If Material Is Spilled Or Released:

Do not create unnecessary airborne dust. Avoid inhalation. Use water mist to reduce dust. Provide ventilation as appropriate. Use personal protection: respiratory, skin, and eyes.

Waste Disposal Methods:

Fly ash is not classified as a RCRA hazardous waste. Material can be disposed of as inert solid in a permitted landfill. Follow applicable federal, state, and local rules.

Precautions To Be Taken In Handling And Storage:

Avoid dust inhalation. Use water and other available means to minimize dusting. Use personal protection. Follow good house keeping and personal hygiene practices.

SECTION 8 - FIRST-AID MEASURES

Emergency First Aid Procedures:

Eye Contact

Flush for 15 minutes with water. Seek medical care as needed to remove particles and treat scratched cornea.

Skin Contact

Wash with mild soap and water.

Inhalation

Remove to fresh air; seek medical attention if respiratory symptoms (coughing, chest tightness, shortness of breath) persist.

SECTION 9 - PREPARATION INFORMATION

Original MSDS Prepared:

ISG Resources, Inc.
1000 Cobb Place Boulevard,
Building 400, Kennesaw,
Georgia 30144

January 1, 2001

MSDS Transcribed:

Pozzolanic International Limited
P.O. Box 950,
Delta, British Columbia,
Canada, V4K 3S6

September 10, 2002

Note: Information herein is based on data considered to be accurate as of date prepared. No warranty or representation, express or implied, is made as to the accuracy or completeness of this data and safety information. No responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

Class CI Fly Ash should only be used by knowledgeable persons.

While the information provided in this material safety data sheet is believed to provide a useful summary of the hazards of Class CI Fly Ash as it is commonly used, the sheet cannot anticipate and provide all of the information that might be needed in every situation. Inexperienced product users should obtain proper training before using this product.

In particular, the data furnished in this sheet does not address hazards that may be posed by other materials mixed with Class CI Fly Ash to produce Class CI Fly Ash products. Users should review other relevant material safety data sheets before working with this Class CI Fly Ash or working on Class CI Fly Ash products, for example, concrete.

No representations or warranties with respect to the accuracy or correctness of this information, or of any kind or nature whatsoever are given, made or intended by Pozzolanic International Limited. No legal responsibility whatsoever is assumed for this information, or for any injuries or damages, however caused which may result from the use of this information. This information is offered solely for informational purposes and is subject to your own independent investigation and verification.